

Data sheet for three-phase Squirrel-Cage-Motors



Ordering data : 1LA7070-4AB12

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Electrical data:

Rated motor voltage :	(1) 230 VD/400 VY, 50 Hz, 460 VY, 60 Hz					
Frequency :	50 Hz		60 Hz			
Rated power :	0.25 kW		0.29 kW			
Rated motor speed :	1350 1/ min		1650 1/ min			
Rated motor torque :	1.8 Nm		1.7 Nm			
Rated motor current (IE) :	VD	VY	VY			
	1.34 A	0.77 A	0.76 A			
Starting / rated motor current :	3.0		3.3			
Breakdown / rated motor	1.9		2.0			
Starting / rated motor torque :	1.9		1.9			
	4/4	3/4	2/4	4/4	3/4	2/4
Efficiency %	61.9%	60.4%	55.9%	61.9%	60.4%	55.9%
Power factor :	0.78	0.72	0.61	0.77	0.71	0.59
Efficiency class :	-/-		-/-			

Mechanical data:

Sound pressure level 50 Hz/60Hz (load) :	44 dB(A)	48 dB(A)
Moment of inertia :	0.00052 kg*m ²	
Bearing DE :	6202 2ZC3	
Bearing NDE :	6202 2ZC3	
Type of bearing :	Floating bearings pre-loaded DE (standard)	
Condensate drainage holes :	No	
Regreasing device :	No	
Lubricants :	Esso Unirex N3	
Grease lifetime/Relubrication interval :	40000 h	
Quantity of grease for relubrication :	null g	
External earthing terminal :	No	
Coating :	Special paint finish RAL 7030 stone gray	

Explosion protection:

Type of protection : without (standard)

Environmental conditions:

Ambient temperature :	-20 °C - +40 °C
Altitude above sea level :	1000 m
Standards and specifications :	IEC, DIN, ISO, VDE, EN

General data:

Frame size	071 M
Type of construction :	(2) IM B14 / V18 / V19, standard flange
Weight in kg, without optional accessories :	4.80 kg
Frame material :	Aluminum
Degree of protection :	IP 55
Method of cooling, TEFC :	IC 411
Vibration class :	A (Standard)
Insulation :	155(F) to 130(B)
Duty type :	S1 - continuous duty
Direction of rotation :	Bi-directional

Terminal box:

Material of terminal box :	Aluminum
Type of terminal box :	gk 030
Contact screw thread :	M4
Max. cross-sectional area :	1.50 mm ²
Cable diameter from ... to ... :	9.00 mm - 17.00 mm
Cable entry :	1xM25x1,5-1xM16x1,5
Cable gland :	2 plugs

Special design: