


## Data sheet for three-phase Squirrel-Cage-Motors



Ordering data : **1LA7133-6AA10**

without (standard)

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Electrical data:

Rated motor voltage :	(1) 230 VD/400 VY, 50 Hz, 460 VY, 60 Hz					
Frequency :	50 Hz		60 Hz			
Rated power :	4.00 kW		4.60 kW			
Rated motor speed :	950 1/ min		1150 1/ min			
Rated motor torque :	40.2 Nm		38.2 Nm			
Rated motor current (IE) :	VD	VY	VY			
	16.35 A	9.40 A	9.20 A			
Starting / rated motor current :	4.5		5.0			
Breakdown / rated motor	2.4		2.4			
Starting / rated motor torque :	2.1		2.1			
	4/4	3/4	2/4	4/4	3/4	2/4
Efficiency %	81.4%	81.4%	80.4%	82.0%	82.0%	81.0%
Power factor :	0.76	0.70	0.58	0.76	0.70	0.58
Efficiency class :	-/-		-/-			

### Mechanical data:

Sound pressure level 50Hz/60Hz (load) :	63 dB(A)	67 dB(A)
Moment of inertia :	0.019 kg*m <sup>2</sup>	
Bearing DE :	6208 2ZC3	
Bearing NDE :	6208 2ZC3	
Type of bearing :	Floating bearings pre-loaded DE (standard)	
Condensate drainage holes :	No	
Regreasing device :	No	
Lubricants :	Esso Unirex N3	
Grease lifetime/Relubrication interval :	40000 h	
Quantity of grease for relubrication :	null g	
External earthing terminal :	No	
Coating :	Special paint finish RAL 7030 stone gray	

### Environmental conditions:

Ambient temperature :	-20 °C - +40 °C
Altitude above sea level :	1000 m
Standards and specifications :	IEC, DIN, ISO, VDE, EN

### General data:

Frame size	132 M
Type of construction :	(0) IM B3 / B6 / B7 / B8 / V5 without canopy
Weight in kg, without optional accessories :	44.00 kg
Frame material :	Aluminum
Degree of protection :	IP 55
Method of cooling, TEFC :	IC 411
Vibration class :	A (Standard)
Insulation :	155(F) to 130(B)
Duty type :	S1 - continuous duty
Direction of rotation :	Bi-directional

### Terminal box:

Material of terminal box :	Aluminum
Type of terminal box :	gk 230
Contact screw thread :	M4
Max. cross-sectional area :	6.00 mm <sup>2</sup>
Cable diameter from ... to ... :	11.00 mm - 21.00 mm
Cable entry :	
Cable gland :	

### Special design: